

Printing date 20.10.2016

Version number 1

Revision: 20.10.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** DAI-EL G-558ES**Article number:** G558ES STD**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

No further relevant information available.

**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

Umeda Center Bldg., 4-12, Nakazaki-Nishi 2-chome, Kita-Ku, Osaka, JAPAN

Phone: (+81) 6-6373-4345 Fax: (+81) 6-6373-4281

**Further information obtainable from:** <http://www.daikin.com/>**1.4 Emergency telephone number:**

Japan: +81-6-6349-7521

China: +86-512-5-232-0949, +86-21-34151689

South Korea: +82-2-568-1722

Americas: +1-256-306-5000

Europe: +49-211-179 225-0

**SECTION 2: Hazard identification****2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

The product is not classified according to the CLP regulation.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008:** Not applicable**Signal word:** Not applicable**Additional information:**

EUH210 Safety data sheet available on request.

**SECTION 3: Composition/information on ingredients****Information on ingredients:**

25190-89-0 Vinylidene fluoride-tetrafluoroethylene-hexafluoropropylene copolymer

49663-94-7 DBU-B

Xi R36

Eye Irrit. 2, H319

1478-61-1 Bisphenol AF

Xi R36

Eye Irrit. 2, H319

Imidazole derivative

T R23; Xn R22

Acute Tox. 2, H330

Acute Tox. 4, H302

**Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Seek medical treatment.**After inhalation:** In case of inhaling decomposed gases: supply fresh air and consult a doctor in case of complaints.**After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

After contact with the molten product, cool rapidly with cold water.

Immediately rinse with warm water and soap.

Consult a doctor in case of complaints.

Printing date 20.10.2016

Version number 1

Revision: 20.10.2016

**Trade name: DAI-EL G-558ES****After eye contact:***Rinse opened eye for several minutes under running water.**Consult an ophthalmologist in case of complaints.***After swallowing:** *If symptoms persist consult a doctor.***4.2 Most important symptoms and effects, both acute and chronic:** *No further relevant information available.***4.3 Indication of any immediate medical attention and special treatment needed:***No further relevant information available.***SECTION 5: Firefighting measures****5.1 Extinguishing media***Suitable extinguishing agents: Use fire extinguishing methods suitable for surrounding conditions.**For safety reasons unsuitable extinguishing agents: No further information available.***5.2 Special hazards arising from the substance or mixture:***Formation of toxic gases is possible during heating or in case of fire.***5.3 Advice for firefighters:****Protective equipment:***Wear self-contained breathing apparatus and protective suit.**Do not inhale explosion gases or combustion gases.***SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures:***Ensure adequate ventilation before entering the area.**Keep out unauthorized persons.**Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).**Avoid contact with eyes and skin.**Do not swallow the product.***6.2 Environmental precautions:** *Do not allow product to reach sewage system or any water course.***6.3 Methods and material for containment and cleaning up:** *No special measures required.***6.4 Reference to other sections:***See Section 8 for information on personal protection equipment.**See Section 13 for disposal information.***SECTION 7: Handling and storage****7.1 Precautions for safe handling:***Ensure good ventilation/exhaustion at the workplace.**Extractors are required on all machines used for thermal processing or powder handling processes.**Do not handle until all safety precautions have been read and understood.***Information about fire - and explosion protection:** *Keep ignition sources away - Do not smoke.***7.2 Conditions for safe storage, including any incompatibilities:****Storage****Requirements to be met by storerooms and receptacles:** *Store in a cool and dry location.***Information about storage in one common storage facility:***See section 10 for information on incompatible materials.***Further information about storage conditions:***Protect from heat and direct sunlight.**Store containers in a well ventilated area.***7.3 Specific end use(s):** *No further relevant information available.***SECTION 8: Exposure controls/personal protection****Additional information about design of technical facilities:** *No further data; see item 7.***8.1 Control parameters** *No further information available.***Ingredients with limit values that require monitoring at the workplace:***The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*

Printing date 20.10.2016

Version number 1

Revision: 20.10.2016

**Trade name: DAI-EL G-558ES****8.2 Exposure controls****Personal protective equipment****General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not eat or drink while working.

Keep away from tobacco products.

**Respiratory protection:**

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases), if the product is heated above 200 °C and toxic gases is formed.

Dust respirator, simplified dust respirator

**Protection of hands:**

Protective gloves

**Material of gloves:** Rubber**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**

Safety glasses

**Body protection:** Protective work clothing**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance**

|                                       |   |
|---------------------------------------|---|
| <b>Form:</b>                          | Solid material<br>Sheet                       |
| <b>Colour:</b>                        | White   |
| <b>Odour:</b>                         | Odourless                                     |
| <b>Odour threshold:</b>               | Not determined.                               |
| <b>pH-value:</b>                      | No further information available.             |
| <b>Melting point/Melting range:</b>   | No further information available.             |
| <b>Boiling point/Boiling range:</b>   | No further information available.             |
| <b>Flash point:</b>                   | Not applicable.                               |
| <b>Flammability (solid, gaseous):</b> | No data.                                      |
| <b>Decomposition temperature:</b>     | No further information available.             |
| <b>Self-igniting:</b>                 | Product is not selfigniting.                  |
| <b>Danger of explosion:</b>           | Product does not present an explosion hazard. |
| <b>Explosion limits:</b>              |   |
| <b>Lower explosive limit:</b>         | No further information available.             |
| <b>Upper explosive limit:</b>         | No further information available.             |
| <b>Vapour pressure:</b>               | No further information available.             |
| <b>Density at 20 °C:</b>              | 1,81-1,90 g/cm <sup>3</sup>                   |
| <b>Relative density</b>               | Not determined.                               |
| <b>Vapour density</b>                 | Not determined.                               |
| <b>Evaporation rate</b>               | Not applicable.                               |

Printing date 20.10.2016

Version number 1

Revision: 20.10.2016

Trade name: DAI-EL G-558ES

**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Partition coefficient (n-octanol/water):** No further information available.

**Viscosity:**

**Dynamic:** Not determined.

**Kinematic:** Not determined.

**9.2 Other information:** No further relevant information available.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

**10.2 Chemical stability**

**Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.

**10.3 Possibility of hazardous reactions:** No dangerous reactions known under normal conditions of use.

**10.4 Conditions to avoid:** Keep away from heat, sparks, flame, high temperature.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:**

As for decomposition products, particulate matters and extremely toxic/corrosive fumes may be generated (HF, carbonyl fluoride, monomers, perfluoroisobutylene).

Decomposition products differ depending on the temperature and conditions.

Organic iodine compounds such as methyl iodide may be generated when iodine which becomes a crosslinking point reacts with decomposed products of organic peroxide.

## SECTION 11: Toxicological information

**11.1 Information on toxicological effects**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:** No further information available.

**Primary irritant effect**

**Skin corrosion/irritation** No further information available.

**Serious eye damage/irritation** No further information available.

**after inhalation:** No further information available.

**Respiratory or skin sensitisation** No further information available.

**Additional toxicological information:**

**General effects:**

Fumes generated during burning may cause "polymer fume fever" (flu-like symptoms such as fever, chill, cough).

This may last for a whole day and night.

Fumes are not absorbed in skin. No sensitizing effect known.

**Effects of hydrogen fluoride:**

Low concentration of hydrogen fluoride may cause feeling of dyspnea, cough, irritation in eyes, nose, throat, fever, chill for 1-2 days.

After that, dyspnea, cyanosis and pulmonary edema may be seen.

High concentration of hydrogen fluoride damages liver and kidney.

**Effects of carbonyl fluoride:**

**Skin:** Irritation or eruption

**Eye:** Ulcer in cornea, conjunctiva

**Respiratory system :** Irritation

**Lung:** Temporary symptoms such as cough, pain, dyspnea

Persons who have experienced lung diseases are vulnerable to toxicity caused by excessive exposure to pyrolysis products

**CMR effects**

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** Based on available data, the classification criteria are not met.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

Printing date 20.10.2016

Version number 1

Revision: 20.10.2016

Trade name: DAI-EL G-558ES

*Chronic study No further information available.***SECTION 12: Ecological information****12.1 Toxicity***Aquatic toxicity: No further relevant information available.***12.2 Persistence and degradability:** *The product is thought to be non-biodegradable.***12.3 Bioaccumulative potential:** *No further relevant information available.***12.4 Mobility in soil:** *No further relevant information available.**Ecotoxicological effects: no data***12.5 Results of PBT and vPvB assessment****PBT:** *No further relevant information available.***vPvB:** *No further relevant information available.***12.6 Other adverse effects:** *No further relevant information available.***SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation:***Landfill disposal is recommended.**In case of incineration, the temperature must be higher than 800 °C.**Treat exhaust gas such as HF in a suitable way.**Disposal must be made according to official regulations.***Uncleaned packaging****Recommendation:** *Disposal must be made according to official regulations.***SECTION 14: Transport information****14.1 UN-Number:****ADR, ADN, IMDG, IATA** *Not applicable***14.2 UN proper shipping name:****ADR, ADN, IMDG, IATA** *Not applicable***14.3 Transport hazard class(es):****ADR, ADN, IMDG, IATA****Class:** *Not applicable***14.4 Packing group:****ADR, IMDG, IATA** *Not applicable***14.5 Environmental hazards:****Marine pollutant:** *No***14.6 Special precautions for user:** *Not applicable.***14.7 Transport in bulk according to Annex II of****MARPOL73/78 and the IBC Code:** *Not applicable.***Transport/Additional information:***Avoid direct sunlight. Make sure of no damage, corrosion, leaks on the receptacles.**Take necessary measures for preventing cargo shift.***UN "Model Regulation":***Not applicable***\* SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture***No further relevant information available.***Labelling according to Regulation (EC) No 1272/2008** *Not applicable***Hazard pictograms** *Not applicable***Signal word** *Not applicable***Hazard statements** *Not applicable***National regulations** *No further information available.***15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

Printing date 20.10.2016

Version number 1

Revision: 20.10.2016

Trade name: DAI-EL G-558ES

**SECTION 16: Other information**

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:** EHS Department

**Contact:** <http://www.daikin.com/>

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

\* **Data compared to the previous version altered.**