

Revision: 23.07.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: <u>DAIFREE MS-175</u> Article number: MS175 **1.2 Relevant identified uses of the substance or mixture and uses advised against:** No further relevant information available.

## 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION: Umeda Center Bldg., 4-12, Nakazaki-Nishi 2-chome, Kita-Ku, Osaka, JAPAN Phone: (+81) 6-6373-4345 Fax: (+81) 6-6373-4281

*Further information obtainable from:* http://www.daikin.com/ *1.4 Emergency telephone number: Japan:* +81-6-6349-7521 *China:* +86-512-5-232-0949, +86-21-34151689 *South Korea:* +82-2-568-1722 *Americas:* +1-256-306-5000 *Europe:* +49-211-179 225-0

# **SECTION 2: Hazard identification**

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



STOT SE 2H371 May cause damage to organs.STOT RE 2H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Acute 1 H400 Very toxic to aquatic life.



Acute Tox. 4 H332 Harmful if inhaled.

	`_`_`_		
2.2 Label element	ts		
Labelling according to Regulation (EC) No 1272/2008:			
The product is classified and labelled according to the CLP regulation.			
Signal word: Danger			
Precautionary statements:			
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
P241	Use explosion-proof electrical/ventilating/lighting equipment.		
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/			
	shower.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P405	Store locked up.		



\*

#### Trade name: DAIFREE MS-175

P501	Dispose of contents/container in accordance with local/regional/natio regulations.	nal/international	
SECTION 3: Composition/information on ingredients			
Information on ingredients:			
	Fluoropolymer	<5%	
CAS: 68551-	15-5 Isononane STOT SE 2, H371; STOT RE 2, H373 Aquatic Acute 1, H400 Acute Tox. 4, H332	≥90%	
CAS: 123-86 Additional in	-4 n-Butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 <b>formation:</b> For the wording of the listed hazard phrases refer to section 16.	<5%	

### **SECTION 4:** First aid measures

#### 4.1 Description of first aid measures

General information: Seek medical treatment.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothes immediately. Immediately wash with water and soap and rinse thoroughly.

Consult a doctor in case of complaints.

After eye contact:

Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing. Consult an ophthalmologist in case of complaints.

#### After swallowing:

Rinse mouth with water. Do not induce vomitting.

Consult a doctor in case of complaints.

4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available.4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media Suitable extinguishing agents: Fire-extinguishing powder CO<sub>2</sub> Foam For safety reasons unsuitable extinguishing agents: Water with full jet 5.2 Special hazards arising from the substance or mixture: Formation of toxic gases is possible during heating or in case of fire. Receptacle may explode when heated. Extremely flammable; can ignite easily with heat, sparks, fire. 5.3 Advice for firefighters: Remove receptacles from area of fire if possible. Protective equipment: Wear self-contained breathing apparatus and protective suit. Do not inhale explosion gases or combustion gases.

### **SECTION 6:** Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures:** Ensure adequate ventilation before entering the area. Stay on the windward side.



Version number 1

Printing date 23.07.2019

Trade name: DAIFREE MS-175

Keep out unauthorized persons. Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection). Avoid contact with eyes and skin. Do not swallow the product. 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars. 6.3 Methods and material for containment and cleaning up: Do not flush with water or aqueous cleansing agents For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly. For a small amount of leakage: Use clean anti-static tools when absorbing the product. For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect. Remove ignition sources immediately. Ground all equipment when the product leaks. There is a danger of explosion. Prepare fire extinguisher in case of emergency. 6.4 Reference to other sections: See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

# 7.1 Precautions for safe handling:

Open and handle receptacle with care. Prevent formation of aerosols. Ensure good ventilation/exhaustion at the workplace. Handle with care. Avoid jolting, friction and impact. Do not handle until all safety precautions have been read and understood. Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Use flame proof electric/lighting devices and ventilation equipment. Ground/bond container and receiving equipment. 7.2 Conditions for safe storage, including any incompatibilities: Storage *Requirements to be met by storerooms and receptacles:* Store in a cool and dry location. Keep containers tightly sealed. Information about storage in one common storage facility: Store away from oxidising agents. See section 10 for information on incompatible materials. Further information about storage conditions: Protect from heat and direct sunlight. Store containers in a well ventilated area. Store locked up. 7.3 Specific end use(s): No further relevant information available.

# SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

**8.1 Control parameters** No further information available. Ingredients with limit values that require monitoring at the workplace:

# CAS: 123-86-4 n-Butyl acetate

OEL (Japan) Long-term value: 475 mg/m<sup>3</sup>, 100 ppm

- PEL (USA) Long-term value: 710 mg/m<sup>3</sup>, 150 ppm
- REL (USA) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm Long-term value: 710 mg/m<sup>3</sup>, 150 ppm
- TLV (USA) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

Revision: 23.07.2019



Version number 1

Printing date 23.07.2019

Trade name: DAIFREE MS-175

Revision: 23.07.2019

8.2 Exposure controls
Personal protective equipment
General protective and hygienic measures:
Wash hands before breaks and at the end of work.
Do not eat or drink while working.
Keep away from tobacco products.
Respiratory protection:
Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.
Use respiratory protective device with organic gas cartridge.
Protection of hands:



Protective gloves

Material of gloves: Rubber Eye protection:

Safety glasses

Body protection: Protective work clothing

### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties General Information Appearance				
Form:	Liquid			
Colour:	Transparent			
	•			
Odour:	Aromatic			
pH-value:	No further information available.			
Melting point/freezing point:	No further information available.			
Initial boiling point and boiling range				
Indial boung point and boung range	. No junner information available.			
Flash point:	21.7 °C (TCC)			
Explosion limits: Lower explosive limit: Upper explosive limit:	No further information available. No further information available.			
Vapour pressure:	No further information available.			
Density at 25 °C: Relative density at 25 °C	0.72-0.75 g/cm <sup>3</sup> 0.73			
Solubility in / Miscibility with water:	No further information available.			
Partition coefficient: n-octanol/water: 9.2 Other information:	No further information available. No further relevant information available.			

# SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

*Thermal decomposition / conditions to be avoided:* To avoid thermal decomposition do not overheat. 10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use. 10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials: Oxidizing agents



Revision: 23.07.2019

Trade name: DAIFREE MS-175

10.6 Hazardous decomposition products: Danger of toxic fluorine based pyrolysis products.

# SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity no data Harmful if inhaled. LD/LC50 values relevant for classification: No further information available. **Primary irritant effect** Skin corrosion/irritation No further information available. Serious eve damage/irritation No further information available. after inhalation: No further information available. Respiratory or skin sensitisation Based on available data, the classification criteria are not met. Other information (about experimental toxicology): No further information available. Subacute to chronic toxicity No further information available. CMR effects Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure May cause damage to organs. STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available. 12.2 Persistence and degradability: No further relevant information available. 12.3 Bioaccumulative potential: No further relevant information available. 12.4 Mobility in soil: No further relevant information available. Ecotoxical effects: no data Remark: Very toxic for fish Additional ecological information: General notes: Very toxic for aquatic organisms 12.5 Results of PBT and vPvB assessment **PBT**: No further relevant information available. Not applicable. vPvB: No further relevant information available. *Not applicable.* 12.6 Other adverse effects: No further relevant information available.

# SECTION 13: Disposal considerations

13.1 Waste treatment methods Recommendation: Disposal must be made according to official regulations.

Uncleaned packaging Recommendation: Disposal must be made according to official regulations.

### **SECTION 14: Transport information**

14.1 UN-Number: ADR, IMDG, IATA 14.2 UN proper shipping name: ADR: IMDG, IATA

UN1866

1866 RESIN SOLUTION RESIN SOLUTION



Trade name: DAIFREE MS-175

Version number 1

Revision: 23.07.2019

14.2 T	
14.3 Transport hazard class(es):	
ADR, IMDG	
Class:	3 Flammable liquids.
Label:	3
IATA	
Class:	3 Flammable liquids.
Label:	3
14.4 Packing group:	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Product contains environmentally hazardous substances. Isononane
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user:	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F- $E$ , $S$ - $E$
14.7 Transport in bulk according to Anne	x II of
MARPOL73/78 and the IBC Code:	Not applicable.
Transport/Additional information:	Avoid direct sunlight. Make sure of no damage, corrosion, leaks or
	the receptacles.
	Take necessary measures for preventing cargo shift.
ADR	51
Limited quantities (LQ):	5L Code: E2
Excepted quantities $(EQ)$	
	Maximum net quantity per inner packaging: 30 ml
Turner out actor own	Maximum net quantity per outer packaging: 500 ml 2
Transport category: Tunnel restriction code:	2 D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
Excepted quantantes (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN1866, RESIN SOLUTION, 3, II
SECTION 15: Regulatory informa	tion

SECTION 15: Regulatory information

\*

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms





Version number 1

Printing date 23.07.2019

Signal word Danger

#### Trade name: DAIFREE MS-175

Revision: 23.07.2019

Bighui word Dung		
_	ing components of labelling:	
Isononane		
Hazard statement	ts	
H225 Highly flam	umable liquid and vapour.	
H332 Harmful if	inhaled.	
H371 May cause	damage to organs.	
H373 May cause	damage to organs through prolonged or repeated exposure.	
H400 Very toxic t	o aquatic life.	
Precautionary sta	atements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P241	Use explosion-proof electrical/ventilating/lighting equipment.	
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.		
P304+P340	<i>IF INHALED: Remove person to fresh air and keep comfortable for breathing.</i>	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/international	
	regulations.	

National regulations No further information available. 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: EHS Department Contact: http://www.daikin.com/ Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 4: Acute toxicity – Category 4 STOT SE 2: Specific target organ toxicity (single exposure) – Category 2 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

\* Data compared to the previous version altered.