

Printing date 30.01.2020 Version number 1 Revision: 30.01.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: <u>OPTOOL UD120</u> Article number: FS-UD120 STD

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

DAIKIN INDUSTRIES, LTD. CHEMICALS DIVISION:

Umeda Center Bldg., 4-12, Nakazaki-Nishi 2-chome, Kita-Ku, Osaka, JAPAN

Phone: (+81) 6-6373-4345 Fax: (+81) 6-6373-4281

Further information obtainable from: http://www.daikin.com/

1.4 Emergency telephone number:

Japan: +81-6-6349-7521

China: +86-512-5-232-0949, +86-21-34151689

South Korea: +82-2-568-1722

Americas: CHEMTREC +1-800-424-9300 (Outside US/Canada: +1-703-527-3887)

Europe: +49-211-179 225-0

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Signal word: Not applicable **Precautionary statements:**

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Information on ingredients:

CAS: 163702-06-5 Ethyl nonafluoroisobutyl ether

45-55%

Aquatic Chronic 4, H413

CAS: 163702-05-4 Ethyl nonafluorobutyl ether

25-35%

Aquatic Chronic 4, H413

15-25%

Fluorocompound

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Seek medical treatment.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Consult a doctor in case of complaints.

After eye contact:

Immediately rinse with a lot of water for several minutes. Remove contact lenses if possible. Continue rinsing. Consult an ophthalmologist in case of complaints.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

Consult a doctor in case of complaints.

4.2 Most important symptoms and effects, both acute and chronic: No further relevant information available.



Printing date 30.01.2020 Version number 1 Revision: 30.01.2020

Trade name: OPTOOL UD120

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable for surrounding conditions.

5.2 Special hazards arising from the substance or mixture:

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters:

Protective equipment:

Wear fully protective suit.

Wear self-contained breathing apparatus and protective suit.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation before entering the area.

Stay on the windward side.

Keep out unauthorized persons.

Wear appropriate protective devices (See Section 8 Exposure Controls/Personal Protection).

Avoid contact with eyes and skin.

Do not swallow the product.

6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.

6.3 Methods and material for containment and cleaning up:

For a small amount of leakage: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders) or collect in an empty container that can be sealed tightly.

For a large amount of leakage: Enclose with banks to avoid outflow. Lead the leakage to a safe place and collect.

6.4 Reference to other sections:

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Do not handle until all safety precautions have been read and understood.

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities:

Storage

Requirements to be met by storerooms and receptacles:

Store in a cool and dry location.

Prevent any seepage into the ground.

Keep containers tightly sealed.

Information about storage in one common storage facility:

Not required.

No further information available.

See section 10 for information on incompatible materials.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacle.

Protect from heat and direct sunlight.

Store containers in a well ventilated area.

Store locked up.

7.3 Specific end use(s): No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters No further information available.



Printing date 30.01.2020 Version number 1 Revision: 30.01.2020

Trade name: OPTOOL UD120

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not eat or drink while working. Keep away from tobacco products.

Respiratory protection:

Respiratory protection providing APF 10,000 required for employees engaged in unenclosed spray applications to which workers may be exposed.

Use respiratory protective device with filters for organic and acid gas (or airline respirators in some cases) if formation of toxic gases is possible while the product is heated.

Use respiratory protective device with organic gas cartridge.

Protection of hands:



Material of gloves: Rubber

Eye protection:



Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance

Form: Fluid

Colour: Clear colorless - light yellow

Odour: Odourless
Odour threshold: Not determined.

pH-value: Not determined.

Melting point/freezing point: No further information available.

Initial boiling point and boiling range: 76 °C

Flash point: Not applicable.
Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower explosive limit:No further information available.Upper explosive limit:No further information available.Vapour pressure:No further information available.

Density at 20 °C:1.43 g/cm³Relative densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.



Printing date 30.01.2020 Version number 1 Revision: 30.01.2020

Trade name: OPTOOL UD120

Solubility in / Miscibility with

water: No further information available.

Partition coefficient: n-octanol/water: No further information available.

Not determined.

Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.

10.3 Possibility of hazardous reactions: No dangerous reactions known under normal conditions of use.

10.4 Conditions to avoid: Keep away from heat, sparks, flame, high temperature.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Danger of toxic fluorine based pyrolysis products.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 163702-06-5 Ethyl nonafluoroisobutyl ether

 $Oral \qquad LD50 \qquad > 2000 \, mg/kg \, (Rat)$

Inhalative LC50/4h 989 mg/l (Rat)

CAS: 163702-05-4 Ethyl nonafluorobutyl ether

 $Oral \qquad LD50 > 2000 \, mg/kg \, (Rat)$

Primary irritant effect Skin corrosion/irritation

No further information available.

CAS: 163702-06-5 Ethyl nonafluoroisobutyl ether

Irritation of skin Primary skin irritation study (Rat)

No irritation

Serious eye damage/irritation

No further information available.

CAS: 163702-06-5 Ethyl nonafluoroisobutyl ether

Irritation of eyes Primary eye irritation study (Rat)

No irritation

after inhalation: No further information available.

Respiratory or skin sensitisation

CAS: 163702-06-5 Ethyl nonafluoroisobutyl ether

Sensitisation Skin Sensitization SI (Guinea pig)

Negative

Based on available data, the classification criteria are not met.

Other information (about experimental toxicology): No further information available.

Subacute to chronic toxicity No further information available.

CMR effects

Germ cell mutagenicity

Not applicable

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.



Printing date 30.01.2020 Version number 1 Revision: 30.01.2020

Trade name: OPTOOL UD120

STOT-repeated exposure

CAS: 163702-05-4 Ethyl nonafluorobutyl ether

Inhalative NOAEL 9000 ppm (Rat)

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 163702-06-5 Ethyl nonafluoroisobutyl ether

 $LC50/96h > 100 \, mg/l \, (Fish)$

EC50/48h > 100 mg/l (Daphnia)

 $EC50/96h > 100 \, mg/l \, (Alga)$

CAS: 163702-05-4 Ethyl nonafluorobutyl ether

 $LC50/96h > 2.75 \, mg/l \, (Fish)$

 $EC50/48h > 2.55 \, mg/l \, (Daphnia)$

EC50/96h 2.32 mg/l (Alga)

12.2 Persistence and degradability: No further relevant information available.

Other information: The product is slightly biodegradable.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

Ecotoxical effects: no data

12.5 Results of PBT and vPvB assessment

PBT:

No further relevant information available.

Not applicable.

vPvB:

No further relevant information available.

Not applicable.

12.6 Other adverse effects: No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation: Disposal must be made according to official regulations.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number:

ADR, ADN, IMDG, IATA Not applicable

14.2 UN proper shipping name:

ADR, ADN, IMDG, IATA Not applicable

14.3 Transport hazard class(es):

ADR, ADN, IMDG, IATA

Class: Not applicable

14.4 Packing group:

ADR, IMDG, IATA Not applicable

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user: Not applicable.



Printing date 30.01.2020 Version number 1 Revision: 30.01.2020

Trade name: OPTOOL UD120

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

Transport/Additional information: Avoid direct sunlight. Make sure of no damage, corrosion, leaks on

the receptacles.

Take necessary measures for preventing cargo shift.

UN "Model Regulation": Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms Not applicable

Signal word Not applicable

Hazard statements

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations No further information available.

Other regulations, limitations and prohibitive regulations: 1

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The product is for the industrial use only. We do not guarantee the safety in case the product is used for the other purposes. When using the product for health-care application or food/feed application, consult us in advance. This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: EHS Department

Contact: http://www.daikin.com/ Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4

* Data compared to the previous version altered.