

Fluoropolymer Coating Powder NEOFLON FEP NC-1515

 TECHNICAL
DATASHEET

FEP powder for excellent corrosion resistance.

Introduction

- NEOFLON FEP NC-1500 grade is a FEP powder for electrostatic spraying.
- NEOFLON FEP NC-1515 makes high build green layers displaying excellent corrosion resistance and heat resistance.
- It is good for linings in chemical industry.

Characteristics

Film appearance	Processing method	Applicable film thickness
Green	Electrostatic spraying	100~2,000μm

Characteristics of the powder

Items	Unit	Data	Method of measurement
Bulk density	g/ml	0.6	JIS K6891
Average particle size	μm	50	Laser diffraction
Melting point of raw material	°C	270	ASTM D2116
MFR of raw material	g/10min	1	ASTM D2116

Characteristics of the coating film

Items	Unit	Data	Method of measurement
Static friction coefficient	-	0.05 – 0.08	Bauden leben steel sheet
Contact angle (Water)	degree	105	Contact angle meter at 25°C
(Hexadecane)		50	
Tensile strength	MPa	26.5 – 32.4	JIS K6888
Elongation	%	310 – 360	JIS K6888

* The numeric values above are typical and not guaranteed.

Handling method/Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

For more information, visit our website.

DAIKIN INDUSTRIES, LTD.

<https://www.daikinchemicals.com/>

tds-nc-1515-E_ver01_Mar_2018
Copyright (C) DAIKIN INDUSTRIES, LTD., 2018