

Fluoropolymer POLYFLON PTFE M-18F

 TECHNICAL
DATASHEET

A fluoro resin suitable for compound with additives such as carbon.

Introduction

- POLYFLON M-18F is a polytetrafluoroethylene virgin granular fine cut resin.
- Compressing the powder and sintering are a general method for use due to its high melt viscosity.
- Suitable for compound material with additives such as carbon.

General physical properties

Items	Unit	Numeric Value	Test method
Average Particle Size	μm	25	ASTM D 4894
Bulk Density	g/L	330	ASTM D 4894
Std Specific Gravity	-	2.16	ASTM D 4894
Tensile Strength	MPa	58	ASTM D 4894
Elongation	%	440	ASTM D 4894
Shrinkage	%	3.7	50Φ × 50h Internal Method
Melt Peak Temperature (Initial)	°C	345	ASTM D 4894
Melt Peak Temperature (Second)	°C	327	ASTM D 4894

* The above numeric values are representative and not guaranteed.

Handling method/Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.

Packing specification

- 25kg

For more information, visit our website.

DAIKIN INDUSTRIES, LTD.

<https://www.daikinchemicals.com/>

tds-m-18F-E_ver01_Mar_2018
Copyright (C) DAIKIN INDUSTRIES, LTD., 2018