

Mold release agent DAIFREE MS-175 / MS-175GK

 TECHNICAL
DATASHEET

DAIFREE MS-175 / MS-175GK is a solvent type coating / mold release agent. It makes a strong thin film on the mold surface where expresses non-stickiness and oil/water repellency.

Introduction

- Applicable for resin mold process.
- Forming a durable and non-stick film layer at room temp.
- PFOA and ozone-depleting substances FREE.

General physical properties

Items	Unit	Numeric Value	Test method
Appearance	-	MS-175 Clear Liquid MS-175GK Yellow liquid	-
Specific Gravity	g/cm ³	MS-175 0.8 MS-175GK 0.95	25°C
Solid Component	Mass%	MS-175 1.5 MS-175GK 25	-
Recommendable Dilution Ratio		1-5 times	-
Principal solvent	-	Butyl Acetate	-
Flash Point	%	22°C (71.6 F)	-

* The above numeric values are representative and not guaranteed.

Handling method/Safety information

- Be sure to read the notes on SDS and labels before use.
- This product is intended for general industry, and therefore its adequacy and safety as a raw material for medical purposes cannot be guaranteed.
- Use petroleum solvent, butyl acetate, ethyl acetate or acetone for dilution.

Packing specification

- MS-175 13kg
- MS-175GK 16kg

For more information, visit our website.

DAIKIN INDUSTRIES, LTD.

<https://www.daikinchemicals.com/>

tds-ms-175-E_ver01_Mar_2018.
Copyright (C) DAIKIN INDUSTRIES, LTD., 2018